

STATUS OF CLAIMS

1. (Cancelled)
2. (Cancelled)
3. (Withdrawn) An automotive suspension system wherein there is provided an upper ball joint system and a lower ball joint system as claimed in claim 10.
4. (Currently Amended) A ball joint as claimed in claim 9 wherein the means for attaching the housing to the a support arm of the ~~a~~ suspension system is an external threads on the external surface of the middle portion of the housing.
5. (Withdrawn) A ball joint as claimed in claim 9 wherein the means for attaching the housing to the support arm of the suspension system is a flange that can be secured to the support arm by at least one detachable pin.
6. (Withdrawn) A ball joint as claimed in claim 5 wherein the pin is a bolt secured by a nut.
7. (Withdrawn) A ball joint as claimed in claim 9 wherein the means for attaching the housing to the support arms of the suspension system is a compression fit of the housing into openings in the support arms.
8. (Previously amended) A ball joint as claimed in claim 9 wherein the internally conformed lower end of the housing comprises plural shallow channels for receiving lubrication therein.
9. (Currently amended) A metal ball joint comprising in combination:
 - (i) an elongated shaft having an upper end and a lower end and having a longitudinal axis running through said upper end and said lower end, said elongated shaft being threaded on the lower end;
 - (ii) a ball rigidly fixed and surmounted on the upper end of the elongated shaft, said ball, at the highest point opposite the upper end of the elongated shaft, having a truncated flat face;
 - (iii) a housing having an outside surface, a middle portion, and a lower end, said housing being internally conformed at the lower end of the housing to seat the ball and provide pivotal movement about the longitudinal axis of the elongated shaft for the ball relative to the housing, said middle portion of the housing being internally threaded to receive a retaining member for the ball therein and said middle portion having a means for attaching the housing to a socket;

(iv) said retaining member having an upper surface and a lower end, said retaining member having a lubricating port located in the upper surface thereof, the lubricating port being openly connected to a duct, said duct providing a passageway for a lubricants from the lubricating port to the truncated flat face of the ball, ~~the lubricant providing the only mechanism for compressing the ball and holding it in the lower end of the housing,~~ the lubricant exerting pressure against the retaining member to maintain pressure on the ball, said retaining member being externally threaded on the retaining member lower end;

(v) the retaining member being fastened in the housing using a set screw into a threaded opening in an upper flange of the retaining member such that the retaining member can be removed from the housing by removal of the set screw, the retaining member maintaining a seal between the ball and the housing via pressure of the lubricant on the truncated flat face of the ball.

10. (Withdrawn) A metal ball joint system comprising in combination:

(i) an elongated shaft having an upper end and a lower end and having a longitudinal axis running through said upper end and said lower end, said elongated shaft being threaded on the lower end;

(ii) a ball rigidly fixed and surmounted on the upper end of the elongated shaft, said ball, at the highest point opposite the attachment of the elongated shaft, having a truncated flat face;

(iii) a housing having an outside surface, a middle portion, and a lower end, said housing being internally conformed at the lower end to seat the ball and provide pivotal movement about the longitudinal axis of the elongated shaft for the ball relative to the housing, said middle portion of the housing being internally threaded to receive the retaining member therein and said middle portion having a means to attach the housing to a support arm of a suspension system;

(iv) a retaining member having an upper surface and a lower end, said retaining member having a lubricating port located in the upper surface thereof, the lubricating port being openly connected to a duct, said duct providing a passageway for lubricants from the lubricating port to the truncated flat face of the ball, said retaining member being externally threaded on the retaining member lower end;

(v) the retaining member being fastened in the housing using a threaded connection that will allow the removal of the retaining member from the housing;

(vi) a socket, said socket comprising a cylindrical housing having an internal surface said internal surface being threaded to receive the housing therein, said socket having a means of attachment for attachment near a terminal end of a carrier for the ball joint system.